

Kosan⁺ and the popular Kosan⁺ Guardian Regulators

Free Freight
on all orders over \$400.
some exceptions apply

additional Kosan⁺ Guardian Series regulators available



Kosan⁺ and Kosan⁺ Guardian Residential & Commercial Regulators

Regulator	BTU Cap.	Inlet	Outlet	Configuration	Case Qty.
First Stage ~ Compact					
984HP-04	1,000,000	1/4" FNPT	1/2" FNPT	Straight	9
984HP-05		POL			
First Stage ~ Full Size					
988HP-05	2,100,000	F.POL	1/2" FNPT	Straight	9
988HP-06	2,250,000		3/4" FNPT		
Second Stage ~ Compact					
988LP-03	800,000	1/2" FNPT	1/2" FNPT	Straight	9
988LP-34	650,000		3/4" FNPT		
988LP-35	500,000		1/2" FNPT	Back Mount	
988LP-36	650,000		3/4" FNPT		
988LP-37	500,000		1/2" FNPT		
Second Stage ~ Full Size					
998LP-01	1,400,000	1/2" FNPT	3/4" FNPT	Straight	12
998LP-02		3/4" FNPT			
998LP-03	1,000,000	1/2" FNPT	3/4" FNPT	Back Mount	12
998LP-33					
998LP-04		3/4" FNPT		Angle	
998LP-34					
998LP-05	920,000			Angle	
998LP-22	1,000,000	1/2" FNPT	1/2" FNPT	Straight	12
998LP-40					
Integral Two-Stage ~ Compact					
988TW-15	750,000	1/4" FNPT	1/2" FNPT	Straight	9
988TW-17		F.POL			3/4" FNPT
988TW-28					
Integral Two-Stage ~ Full Size					
998TW-13	1,400,000	F.POL	3/4" FNPT	Straight	12
998TW-11		1/4" FNPT			
998TW-23	1,400,000	1/4" FNPT	3/4" FNPT 2 psi		

New

Guardian
Guardian

Guardian

Guardian

Guardian



- Italian design - engineered for the American market
- UL Listed and all standard approvals
- Superior performance, 100% tested - dimensionally interchangeable
- Lower profile for better dome lid clearance - perfect for underground tanks
- 1/8" pressure taps with #54 orifice on inlets and outlets of all regulators
- Seal on body flange to identify tampering
- More vent and inlet/outlet configurations available
- Ten year warranty . . . recommended replacement is 25 years
- Molded diaphragm and large surface GLT Viton seat disc
- Temperature rating from -40° F to 130° F
- Screened inlets on all second-stage regulators
- Stainless steel screws and internal linkage assemblies
- All aluminum body, corrosion resistant finish

